

Pipe Insulation (FM Approval Class Number 4924)

Mechanical piping systems such as those used in heating, ventilating, air conditioning, or refrigeration at temperatures not exceeding 220°F (104°C) sometimes need to be insulated for maximum operational efficiency. The insulations listed below have been tested and found to be acceptable in and of themselves, without needing automatic sprinkler protection.

Each insulation should be used with regard for the size and shape limitations, if any, following their respective listings.

Pipe Insulation

KAIFLEX KKplus

KAIFLEX KKplus

KAIFLEX KKplus thermal insulation is a black flexible, elastomeric thermal insulation product

KAIFLEX KKplus tubular insulation is supplied in wall thicknesses from 0.28 in. (7mm) to 1.65 in. (42 mm), for application over pipes with an external diameter 0.25 in (6 mm) to 5.9 in. (150 mm) and requires KAIFLEX Special Adhesive.

KAIFLEX KKplus sheet insulation is supplied in flat sheet, maximum 0.25 in. (6mm) to 1.96 in. (50 mm) thick for application over pipes and ducts and requires KAIFLEX Special Adhesive.

Company Name:	Kaimann GmbH
Company Address:	Hanstrabe 2-5, D-33161 Hovelhof
Company Website:	http://www.kaimann.de
Listing Country:	Germany
Certification Type:	FM Approved