

Pipe Insulation (FM Approval Class Number 4924)

Mechanical piping systems such as those used in heating, ventilating, air conditioning, or refrigeration at temperatures not exceeding 220°F (104°C) sometimes need to be insulated for maximum operational efficiency. The insulations listed below have been tested and found to be acceptable in and of themselves, without needing automatic sprinkler protection.

Each insulation should be used with regard for the size and shape limitations, if any, following their respective listings.

Pipe Insulation

KAIFLEX KKplus-SK

KAIFLEX KKplus-SK

KAIFLEX KKplus-SK thermal insulation is a black flexible, elastomeric thermal insulation product furnished with a pressure sensitive tape adhesive.

KAIFLEX KKplus-SK tubular insulation is supplied in wall thicknesses from 0.28 in. (7mm) to 1.65 in. (42 mm), presilt with two sided pressure sensitive tape, for application over pipes with an external diameter 0.25 in (6 mm) to 5.9 in. (150 mm)

KAIFLEX KKplus-SK sheet insulation is supplied in flat sheet with a pressure sensitive tape adhesive applied on one face, maximum 0.25 in. (6mm) to 1.96 in. (50 mm) thick for application over pipes and ducts.

Company Name:	Kaimann GmbH
Company Address:	Hanstrabe 2-5, D-33161 Hovelhof
Company Website:	http://www.kaimann.de
Listing Country:	Germany
Certification Type:	FM Approved