

User Manual

MultiFill ECO



1

MultiFill ECO is compatible with 300 ml foil-packed Multimastic SP or Multisealant GR.

Before you start, make sure you have all parts of the MultiFill ECO and a sealant gun ready.¹

5

Insert the loaded MultiFill ECO into your sealant gun. It is now ready for use.

2

Place the 300 ml foil pack into the MultiFill ECO cartridge.

6

As you use the sealant, the foil will be squeezed forward and crumple up inside the cartridge.

3

Gently pull the tip of the foil pack out from the top of the cartridge. Use scissors to cut off just the very end of the tip.

Do not use a knife. Avoid cutting too much and damaging the rest of the foil.

7

When the foil pack is empty, remove the MultiFill ECO from the gun. Take out the top cover and gently pull out the used, crumpled foil.

Do not use a knife to remove the foil. Use your fingers.

4

Put the top cover in place and screw the nozzle onto the MultiFill ECO, on the side where you cut the foil pack.

8

Flip the MultiFill ECO and insert a new foil pack. MultiFill ECO is now ready for another use.²

¹ MultiFill ECO can be used with a standard sealant gun.

² MultiFill ECO can be used up to 90 times.



For use and for more information about an application, refer to the Mulcol documentation, local and international approvals. See the **Mulcol Fire Protection app** for the correct application in combination with fire resistance, or use our selector at www.mulcol.com For professional use only.



MULCOL
INTERNATIONAL