

T-301 - Armert Aluminiumstape

Description	Enkelttidig tape betående av ren aluminiums folie, forsterket med 5 mm ² nettarmoring og løsningsmiddelbasert gummi lim. Har dekkpapi.
Product properties	Lett å bruke med godt feste på de fleste underlag. Kan brukes på alle strukturer og profiler. Nettarmoringen forbedrer dens motstand mot mekanisk skade. Sluttheft har høy skjær og strekkfasthet.
Specifications	Brannklasse : Samsvarer med klasse "0" BS 476 part 7 Klasse 1
Applications	Spesialtape for diffusjonstett forsegling av lamellmatter og rørskåler og generelle applikasjoner for tetting innen ventilasjon og luftkondisjonering. Tapen har gode prestanda ved isolering, støv og fukt samt god brannbeskyttelse. Ikke egnet for bruksområder hvor det er forbundet med mekanisk spenning / stress. Her anbefales fleksible tetningsmasser.
Storage and ageing	1 år lagringstid dersom lagret i original emballasje og innendørs romtemperetur (+ 20C) samt luftfuktighet 50 %.. Unngå direkte sollys.
Applying tips	Alle overflater skal være rengjort og fri for støv , fett og fukt. For rengjøring anbefales det å bruke Isopropyl - Alkohol oppløsning,og påført med trykk.



TECHNICAL DATA

Carrier	Aluminium	
Adhesive	Rubber	
Colour	Aluminium	
Liner	Paper silicone coated	
Weather resistant	Yes	
UV resistant	Yes	
Ageing resistant	Yes	
Adhesion on stainless steel	25 N/25mm	5,71 Lbs/inch
Tensile strength length	80 N/25mm	18,3 Lbs/inch
Elongation length	11 %	
Service temperature	Between -10 and 90 °C	Between 14 and 194 °F
Application temperature	Minimum -5 °C	Minimum 23 °F
Water vapour transmission rate	0,015 g/m ² /24h	3,96E-05 lb/yard ² /24h

Disclaimer: Values shown in this document are averages only. For legal reasons, we emphasize that the information on this data is available "as is" and that Stokvis Tapes, an ITW company, gives no guarantees with respect to the accuracy and completeness nor with respect to interpretations made on the basis of this information.

See our applicable delivery conditions. Each user should conduct his own tests to determine the suitability of the product for his intended use and shall assume all risks and liability in connection therewith. Stokvis Tapes cannot be held liable for any damages resulting from the unsuitability of the product. Many factors beyond the control of Stokvis Tapes may affect the use and performance of the product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluates the Stokvis Tapes product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

The information is available to the user for viewing, copying and distributing, provided that Stokvis Tapes, an ITW company, is always quoted as the source. The information is intended solely for informational and non-commercial use.

Intellectual property: Stokvis Tapes, an ITW company, reserves all rights regarding this document and the information contained herein. Reproduction, use or disclosure to third parties without express permission is strictly forbidden.