

KAIFINISH - Acrylic paint

Quality features – characteristics:

KAIFINISH can be used indoors for optical reasons. Outdoors the insulation must be painted after 3 days at the latest.

KAIFINISH is weatherproofed and age resistant. It is known for excellent flexibility, quick drying and outstanding bending. KAIFINISH is nearly odourless.

Instructions for application:

The insulation must be clean, dry and grease-free, dirty surfaces must be cleaned using Kaiflex CLEANER. The ambient temperature during application should not be less +10 °C or exceed +30 °C. At least one prime and one finish coat must be applied, stir paint well and apply undiluted. Application by brush or by roller is recommended. Give two hours at the least in between first and second coat. At a temperature of +20 °C KAIFINISH is completely dry after some 6 hours (depending on the thickness of the coat). Immediately after use, the painting tools can be thoroughly cleaned with water. Apply 250ml/m²/coat KAIFINISH at least to guarantee complete protection.

Shelf life: at least 1 year. With a view to external influences the protective function of the coats should be verified at regular intervals, at least every 2 years a new finish coat must be applied.

Safety data:

S 02: Keep away from children.

S 51: To be used in thoroughly ventilated areas only.

Completely emptied cans should be recycled. Any cans with residues must be returned to a collection point for waste lacquers and paint.