



**Newtex Industries, Inc.**

Phone: 585-924-9135

Toll-Free: 800-836-1001

E-mail: [sales@newtex.com](mailto:sales@newtex.com)

Website: [www.newtex.com](http://www.newtex.com)

## Product Data Sheet

### Product Information

---

<b>Category</b>	ZetexPlus Fabric
<b>Style</b>	A-600
<b>Weave</b>	1 x 1 Plain
<b>Finish/Coating</b>	ZetexPlus
<b>Ends x Picks</b>	20 x 14

<b>Physical Property</b>	<b>English Units</b>	<b>Metric Units</b>
<b>Weight (Finished)</b>	18.0 oz/yd <sup>2</sup>	610.3 g/m <sup>2</sup>
<b>Thickness</b>	32 mils	0.81 mm
<b>Break Strength</b> (ASTM D5035-1" Strip)	Warp: 380 lbsf Weft: 258 lbsf	Warp: 173 N Weft: 117 N
<b>Abrasion Resistance</b> (Taber Abrasion - H-18 wheel, 500 g., vacuum 50%)		1500 rubs
<b>Flame Resistance (FED 191A - 5903.2)</b>		Char Length – 0 in. After Flame – 0 sec. Afterglow – 1.5 sec.

### Other Information

---

<b>Available Widths</b>	40 in, 60 in
-------------------------	--------------

For additional Questions, please e-mail [tech@newtex.com](mailto:tech@newtex.com)